



5611 Universal Drive Memphis, TN 38118
 PH: 901-795-1943 FX: 901-360-9580 Toll Free: 800-458-1560

Product Information

6043

Water Based Contact Adhesive

Physical Properties

| | |
|-----------------------------|---------------------------------------|
| Base | Synthetic Rubber & Resin |
| Color | White or Pink |
| Solids | 48% to 54% |
| Wt. per Gal..... | 9.1 to 9.2 Lbs. |
| Viscosity..... | 200-1000 cps @ 75 deg. F. |
| Chalking Temp..... | N/A |
| pH Value..... | N/A |
| Shelf Life | 6 Months in Unopened Containers |
| Clean Up | Water While Wet / Hot Soapy Water Dry |
| Open Tack Time | 15 to 30 Minutes After Drying |
| Storage Temperature | 50 to 90 ° F |
| Freeze Thaw Stability | None! KEEP FROM FREEZING |
| Solvent | Water |

Performance Characteristics

1. Ease of Use
2. Uniform Results
3. Solvent Free

Product Description

6043 is a versatile, premium waterborne contact adhesive developed to provide excellent bonds when applied by conventional roll coaters and glue spreaders or by air or airless spray equipment.

This adhesive may be used for bonding decorative laminates, plastics, flakeboard, plywood and etc. to desk, counter and cabinet tops and for bonding a wide variety of skins and cores in laminated panel construction. It will not cause roll collapse when applied to expanded polystyrene core materials. 6043 adhesive can be used in post forming applications.

Surface Preparation: All surfaces must be clean, dry and free of oil, release agents and other contaminants prior to adhesive application.

Stir well before using

Read MSDS before attempting to use this product.