



SAFETY DATA SHEET

Tensorgrip P329 CA Compliant PSA

1. Identification

Product identifier

Product name Tensorgrip P329 CA Compliant PSA
Product number USA

Recommended use of the chemical and restrictions on use

Application Canister Spray Adhesive

Details of the supplier of the safety data sheet

Supplier Quin Global
 5710 F St
 (402) 731 3636
 (402) 731 1473
 marketing.us@quin-global.com

Emergency telephone number

Emergency telephone Chemtrec: 1 800 424 9300 (Mon - Fri) 09:00 - 16:00

2. Hazard(s) identification

Classification of the substance or mixture

Physical hazards Flam. Aerosol 2 - H223 Press. Gas, Compressed - H280
Health hazards Acute Tox. 4 - H302 Skin Irrit. 2 - H315 Eye Irrit. 2A - H319 STOT SE 3 - H336 Asp. Tox. 1 - H304
Environmental hazards Aquatic Chronic 2 - H411

Human health The liquid may be irritating to eyes, respiratory system and skin. Symptoms following overexposure may include the following: Headache. Dizziness. Nausea, vomiting.

Label elements

Pictogram



Signal word

Danger

Hazard statements

H223 Flammable aerosol.
 H280 Contains gas under pressure; may explode if heated.
 H302 Harmful if swallowed.
 H304 May be fatal if swallowed and enters airways.
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.
 H411 Toxic to aquatic life with long lasting effects.

Tensorgrip P329 CA Compliant PSA

Precautionary statements

P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P302+P352 If on skin: Wash with plenty of water.
 P304+P340 If inhaled: Remove person to fresh air and keep comfortable for breathing.
 P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P312 Call a poison center/doctor if you feel unwell.
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Contains Methyl Acetate, Cyclohexane

Other hazards

This product does not contain any substances classified as PBT or vPvB.

3. Composition/information on ingredients

Substances

Mixtures

Methyl Acetate CAS number: 79-20-9	30-60%
Classification Flam. Liq. 2 - H225 Acute Tox. 4 - H302 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Eye Irrit. 2A - H319 STOT SE 3 - H336	
Cyclohexane CAS number: 110-82-7 M factor (Acute) = 1 M factor (Chronic) = 1	10-30%
Classification Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 STOT SE 3 - H336 Asp. Tox. 1 - H304 Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410	

The Full Text for all Hazard Statements are Displayed in Section 16.

4. First-aid measures

Description of first aid measures

General information Remove affected person from source of contamination. Place unconscious person on their side in the recovery position and ensure breathing can take place. Get medical attention if any discomfort continues.

Inhalation Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Get medical attention.

Tensorgrip P329 CA Compliant PSA

Ingestion	Get medical attention immediately. Never give anything by mouth to an unconscious person. Do not induce vomiting. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing.
Skin Contact	Remove affected person from source of contamination. Remove contaminated clothing. Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.
Eye contact	Remove any contact lenses and open eyelids wide apart. Only remove contact lenses if the person is conscious, coherent and they can remove them themselves. If adhesive bonding occurs, do not force eyelids apart. Continue to rinse for at least 15 minutes. If in doubt, get medical attention promptly. Show this Safety Data Sheet to the medical personnel.
<u>Most important symptoms and effects, both acute and delayed</u>	
Inhalation	May cause coughing and difficulties in breathing. May cause eye and respiratory system irritation. Overexposure may depress the central nervous system, causing dizziness and intoxication.
Ingestion	Aspiration hazard if swallowed. May be fatal if swallowed and enters airways. Ingestion may cause severe irritation of the mouth, the esophagus and the gastrointestinal tract. May Cause the following effects: Gastrointestinal symptoms, including upset stomach. Central nervous system depression. Nausea, vomiting. Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis.
Skin contact	May be absorbed through the skin. Product has a defatting effect on skin. The liquid is irritating to eyes and skin. A single exposure may cause the following adverse effects: Dryness and/or cracking.
Eye contact	Causes serious eye irritation. Burns can occur. A single exposure may cause the following adverse effects: Pain. Conjunctivitis, irritation, tearing. Prolonged or repeated exposure may cause the following adverse effects: Irritation of eyes and mucous membranes. Prolonged contact causes serious eye and tissue damage.

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media Extinguish with alcohol-resistant foam, carbon dioxide or dry powder.

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

Special hazards arising from the substance or mixture

Specific hazards Pressurized container: Must not be exposed to temperatures above 50°C/120°F. Containers can burst violently or explode when heated, due to excessive pressure build-up. Vapors are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back.

Advice for firefighters

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions For personal protection, see Section 8. No smoking, sparks, flames or other sources of ignition near spillage.

Environmental precautions

Tensorgrip P329 CA Compliant PSA

Environmental precautions Avoid discharge into drains. Contain spillage with sand, earth or other suitable non-combustible material.

Methods and material for containment and cleaning up

Methods for cleaning up Stop leak if possible without risk. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Avoid the spillage or runoff entering drains, sewers or watercourses. Absorb in vermiculite, dry sand or earth and place into containers. Wash thoroughly after dealing with a spillage.

7. Handling and storage

Precautions for safe handling

Usage precautions Avoid contact with skin and eyes. Keep away from heat, sparks and open flame. Provide adequate ventilation. Avoid inhalation of vapors. Use approved respirator if air contamination is above an acceptable level. Container must be kept tightly closed when not in use. Use explosion proof electric equipment. Avoid discharge into drains or watercourses or onto the ground.

Advice on general occupational hygiene Do not eat, drink or smoke when using this product.

Conditions for safe storage, including any incompatibilities

Storage precautions Keep away from heat, sparks and open flame. Keep container tightly closed. Keep only in the original container. Pressurized container: Must not be exposed to temperatures above 50°C/120°F

Specific end uses(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

8. Exposure Controls/personal protection

Control parameters

Occupational exposure limits

Methyl Acetate

Long-term exposure limit (8-hour TWA): ACGIH 200 ppm

Short-term exposure limit (15-minute): ACGIH 250 ppm

Long-term exposure limit (8-hour TWA): OSHA 200 ppm 610 mg/m³

Cyclohexane

Long-term exposure limit (8-hour TWA): ACGIH 100 ppm

ACGIH = American Conference of Governmental Industrial Hygienists.

OSHA = Occupational Safety and Health Administration.

Exposure controls

Protective equipment



Appropriate engineering controls

This product must not be handled in a confined space without adequate ventilation. Avoid inhalation of vapors and spray/mists. As this product contains ingredients with exposure limits, process enclosures, local exhaust ventilation or other engineering controls should be used to keep worker exposure below any statutory or recommended limits, if use generates dust, fumes, gas, vapor or mist.

Eye/face protection Wear chemical splash goggles.

Tensorgrip P329 CA Compliant PSA

Hand protection	Use protective gloves.
Other skin and body protection	Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapor contact.
Hygiene measures	DO NOT SMOKE IN WORK AREA! Wash hands at the end of each work shift and before eating, smoking and using the toilet. Wash promptly with soap and water if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.
Respiratory protection	Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit. If exposure levels are likely to be exceeded, use a full face mask fitted with an organic AXP3 filter for short term low level exposures. For long term or high level exposures, compressed airline breathing apparatus should be used.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

Appearance	Aerosol. Liquid
Color	Red. Clear
Odor	Organic solvents.
Initial boiling point and range	57.5°C/135°F @
Flash point	-18°C/-0.38°F CC (Closed cup).
Upper/lower flammability or explosive limits	Upper flammable/explosive limit: 16 g/100 g Lower flammable/explosive limit: 1 g/100 g
Relative density	.93
Solubility(ies)	Negligibly soluble in water
Volatile organic compound	This product contains a maximum VOC content of 80 g/l.

10. Stability and reactivity

Stability	Stable at normal ambient temperatures and when used as recommended.
Conditions to avoid	Avoid heat, flames and other sources of ignition. Avoid contact with the following materials: Oxidizing agents. Reducing agents.
Hazardous decomposition products	Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO ₂). Hydrogen chloride (HCl). Nitrous gases (NO _x).

11. Toxicological information

Information on toxicological effects

Acute toxicity - oral

ATE oral (mg/kg) 1,022.49

Acute toxicity - dermal

ATE dermal (mg/kg) 2,249.49

Acute toxicity - inhalation

ATE inhalation (vapours mg/l) 22.49

Toxicological information on ingredients.

Tensorgrip P329 CA Compliant PSA

Methyl Acetate

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 5,000.0

Species Rat

ATE oral (mg/kg) 500.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 2,000.0

Species Rat

ATE dermal (mg/kg) 1,100.0

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ vapours mg/l) 49.28

Species Rat

ATE inhalation (vapours mg/l) 11.0

Cyclohexane

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 12,705.0

Species Rat

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 2,000.0

Species Rabbit

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ vapours mg/l) 34,000.0

Species Rat

Serious eye damage/irritation

Serious eye damage/irritation Slightly irritating.

Aspiration hazard

Aspiration hazard May be fatal if swallowed and enters airways.

Inhalation May be harmful if inhaled. Causes respiratory tract irritation. Vapours may cause drowsiness and dizziness.

Ingestion May be harmful if swallowed. Aspiration hazard if swallowed.

Tensorgrip P329 CA Compliant PSA

Skin Contact May be absorbed through the skin. Causes skin irritation.

Eye contact Causes eye irritation.

12. Ecological Information

13. Disposal considerations

Waste treatment methods

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

14. Transport information

Air transport notes Cargo aircraft only. <75kg

UN Number

UN No. (DOT) 3501

UN No. (ICAO) 3501

UN proper shipping name

Proper shipping name (DOT) Chemical Under Pressure, Flammable, N.O.S. (Methyl Acetate, Cyclohexane)

Transport hazard class(es)

DOT hazard class 2.1

Transport labels



Packing group

Not applicable.

15. Regulatory information

US Federal Regulations

SARA (311/312) Hazard Categories

Yes.

Methyl Acetate

Fire
Acute
Chronic
Health hazard

US State Regulations

Massachusetts "Right To Know" List

The following ingredients are listed or exempt:

Methyl Acetate

Present

New Jersey "Right To Know" List

The following ingredients are listed or exempt:

Tensorgrip P329 CA Compliant PSA

Methyl Acetate

Present.

Pennsylvania "Right To Know" List

The following ingredients are listed or exempt:

Methyl Acetate

Present.

Inventories

US - TSCA

The following ingredients are listed or exempt:

Methyl Acetate

Present.

16. Other information

Revision date	11/6/2015
Revision	1
Supersedes date	8/11/2014
SDS No.	21466
Hazard statements in full	H223 Flammable aerosol. H225 Highly flammable liquid and vapor. H280 Contains gas under pressure; may explode if heated. H302 Harmful if swallowed. H304 May be fatal if swallowed and enters airways. H312 Harmful in contact with skin. H315 Causes skin irritation. H319 Causes serious eye irritation. H332 Harmful if inhaled. H336 May cause drowsiness or dizziness. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects.
ACA HMIS Health rating.	Moderate hazard. (2)
ACA HMIS Flammability rating.	Ignites easily. (3)
ACA HMIS Physical hazard rating.	Normally stable. (0)
ACA HMIS Personal protection rating.	B

The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. Given the variety of factors that can affect the use and application of this product, many of which are solely within the user's knowledge and control, the user is responsible for determining whether the manufacturer of this product is fit for a particular purpose and suitable for users' method of use or application. It is essential that the user evaluate this product, not the manufacturer, to determine whether it is fit for a particular purpose and suitable for users' method of use or application