

**TECHNICAL DATA SHEET**  
**ULTRA-HIGH PERFORMANC FOAM LAMINATING ADHESIVE**  
**FT-72050**

**DESCRIPTION**

**FT-72050** is an ultra-high solids, EVA adhesive designed to provide excellent setting speed, wet tack, machining characteristics, film clarity, adhesion to a variety of substrates, and heat resistance.

<b>POLYMER TYPE</b>	<b>EVA</b>
<b>APPEARANCE</b>	<b>WHITE</b>
<b>SOLIDS</b>	<b>70 % MIN</b>
<b>pH</b>	<b>4.0-5.5</b>
<b>VISCOSITY</b>	<b>5000 ± 10% Cps @ 76°F</b>
<b>FREEZE/THAW STABILITY</b>	<b>PROTECT FROM FREEZING</b>

**Clean-up Procedure**

Whenever possible, clean up product before it dries, using warm water. If dry, use hot water and scraper.

**Freezing Sensitivity**

Store above 40 °F (4 °C).

**Storage Life**

For best results, we recommend that the product be used within six months

**FT-72050** is not hazardous by definition FDA Food Additive Regulation 21CFR175.105. We recommend that you make your own determination on the suitability of **FT-72050** for your particular application. We also recommend that you periodically verify the regulatory status of **FT-72050**.